



## AUTOMATIC TRANSMISSION FLUID

**For use in vehicles previously serviceable by DEXRON<sup>®</sup> III/MERCON<sup>®</sup> brands  
 Suitable where Ford ESP-M2C138CJ or ESP-M2C166H is specified  
 Meets Requirements for Allison C-4**

### PRODUCT DESCRIPTION

FormulaShell<sup>®</sup> Automatic Transmission Fluid is a premium quality automatic transmission fluid for use in both passenger cars and light trucks requiring a fluid that was previously serviceable by the General Motors DEXRON<sup>®</sup> III or Ford MERCON<sup>®</sup> specifications.

FormulaShell<sup>®</sup> Automatic Transmission Fluid is recommended for power steering units specifying either type of fluid, and can be used in Allison Powershift transmissions or other torque converters requiring an Allison C-3 or C-4 fluid.

FormulaShell<sup>®</sup> Automatic Transmission Fluid is a high viscosity index product and offers good oxidation stability, corrosion prevention, foam resistance, and controlled frictional properties. This fluid also provides good seal compatibility, wear protection, and smoother shifting.

### TYPICAL PHYSICAL AND CHEMICAL PROPERTIES FORMULASHELL<sup>®</sup> AUTOMATIC TRANSMISSION FLUID

TEST	TYPICAL RESULTS
API Gravity @ 60° F (15.6° C)	32.8
Specific Gravity @ 60° F (15.6° C)	0.8613
Flash Point, °C (°F)	206 (403)
Pour Point, °C (°F), Max.	-51 (-60)
Color	RED
Viscosity @ 40° C, cSt	35.05
Viscosity @ 100° C, cSt	7.25
Viscosity @ 100° F (SUS)	177.8
Viscosity @ 210° F (SUS)	50.4
Viscosity Index	177
Brookfield Viscosity @ -40° C, cP	16,850
Material Number	
12/1 Quart case	5301012031
5 Gallon Pail	5301005203
16 Gallon Keg	5301000016
55 Gallon Drum	5301000055
Bulk Gallons	5301000001