



TEXACO MARFAK[®] MULTIPURPOSE

2

CUSTOMER BENEFITS

Texaco Marfak Multipurpose delivers value through:

- **Good water resistance** — Provides lubrication in the presence of water.
- **Good corrosion protection** — Inhibited to protect gear and bearing surfaces.
- **Good oxidation stability** — Helps to ensure long life in storage and in use.
- **Simplified lubrication** — One grease designed to satisfy most general purpose, non-EP grease requirements.

FEATURES

Texaco Marfak Multipurpose is manufactured using selected, highly refined medium viscosity index base oils, a lithium 12-hydroxystearate thickener, and rust and oxidation inhibitors.

It is work stable and resists separation or throw out from antifriction bearings. It has a low oil bleeding tendency under pressure and is pumpable at low temperatures.

APPLICATIONS

Texaco Marfak Multipurpose satisfies general automotive and industrial applications that do not require the use of an EP grease.

TYPICAL TEST DATA

NLGI Grade	2
Product Number	220958
MSDS Number	8962
Operating Temperature, °C(°F) Minimum ¹ Maximum ²	-20(-29) 121(250)
Penetration, at 25°C(77°F) Worked Worked (10000X), % Change	280 5
Dropping Point, °C(°F)	188(370)
Copper Corrosion	1B
Thickener, % Type	7.5 Lithium
Viscosity, Kinematic* cSt at 40°C cSt at 100°C	220 18.1
Viscosity, Saybolt* SUS at 100°F SUS at 210°F	1200 93
Flash Point, °C(°F)*	198(388)
Pour Point, °C(°F)*	-12(+10)
Texture	Buttery
Color	Brown

Typical test data are average values only. Minor variations which do not affect product performance are to be expected in normal manufacturing.

- ¹ Minimum operating temperature is the lowest temperature at which a grease, already in place, could be expected to provide lubrication. Most greases cannot be pumped at these minimum temperatures.
 - ² Maximum operating temperature is the highest temperature at which the grease could be used with frequent (daily) relubrication.
- * Determined on mineral oil extracted by vacuum filtration.