



TEXACO MULTIFAK[®] HD

00

CUSTOMER BENEFITS

Texaco Multifak HD delivers value through:

- **Semi-fluid grease properties** provide a thick film of lubricant to critical parts.
- **Low temperature lubrication.**
- **Excellent rust and corrosion protection**
- **Tacky consistency** reduces the risk of water washout.

FEATURES

Texaco Multifak HD is a lithium based semi-fluid grease specially formulated with a high viscosity base oil, and an additive package that contains inhibitors and tackifiers.

APPLICATIONS

Texaco Multifak HD is recommended for gear drives that specify an NLGI 00 grease. These include large mowing machines pulled behind tractors and gearboxes in large mixers.

Texaco Multifak HD is unsuitable for applications requiring an extreme pressure grease.

It is recommended for gear drives specifying a semi-fluid grease, including those manufactured by:

- Jacobsen Division of Textron
- NORD Gear Corporation

TYPICAL TEST DATA

NLGI Grade	00
<i>Product Number</i>	221988
<i>MSDS Number</i>	9006
Operating Temperature, °C(°F) Minimum ¹ Maximum ²	-29(-20) 121(250)
Penetration, at 25°C(77°F) Worked Worked (10,000X), % Change	415 4
Dropping Point, °C(°F)	166(331)
Rust Protection	Pass
Thickener, % Type	1.9 Lithium
Viscosity, Kinematic* cSt at 40°C cSt at 100°C	680 34.0
Viscosity, Saybolt* SUS at 100°F SUS at 210°F	3709 167
Viscosity Index*	78
Texture	Tacky
Color	Brown

Typical test data are average values only. Minor variations which do not affect product performance are to be expected in normal manufacturing.

- ¹ Minimum operating temperature is the lowest temperature at which a grease, already in place, could be expected to provide lubrication. Most greases cannot be pumped at these minimum temperatures.
- ² Continuous service maximum.

* Determined on mineral oil extracted by vacuum filtration.