



# TEXACO MULTIGEAR<sup>®</sup> EP

## SAE 80W-90, 85W-140

### CUSTOMER BENEFITS

Texaco Multigear EP oils deliver value through:

- **Improved durability** — Specially formulated to stand up to the demands of severe service applications.
- **Extended gear life** — Extreme pressure properties protect hypoid and other types of gears from scuffing and wear under heavily loaded conditions.
- **Long lubricant life** — Outstanding thermal and oxidation stability allow high temperature operation with long lubricant life without the formation of sludge and deposits.
- **All-weather protection** — Multiviscosity characteristics assure proper gear lubrication at both low and high ambient temperatures.
- **Corrosion and rust protection** — Effective inhibitor package prevents rusting or corrosion of gears and bearings surfaces.

### FEATURES

Texaco Multigear EP oils are multipurpose lubricants.

They are made with:

- highly refined base stocks.
- a carefully balanced additive package to provide maximum gear protection, long lubricant life and excellent field performance.
- sulfur-phosphorus extreme pressure additives that provide superior thermal and oxidation stability.
- rust and corrosion inhibitors, a foam inhibitor, and a pour point depressant.

The highly refined base stocks and various inhibitors in the additive package assure a well-balanced lubricant and long gear and bearing life with maximum durability.

### APPLICATIONS

Texaco Multigear EP oils are recommended for use in all spiral bevel and hypoid differentials, power dividers, and oil-lubricated steering axle wheel bearings.

They are designed for complete refill and make-up of all passenger car, light duty and heavy duty truck transmissions, conventional differentials and steering gears.

Their multiviscosity characteristics allow their use in equipment operating over a broad ambient temperature range. This means good cold flow properties and gear protection.

Texaco Multigear EP oils meet the performance requirements of:

- **API Service Categories** MT-1, GL-4, and GL-5
- are qualified for **SAE J 2360** (formerly known as MIL-PRF-2105E)

They also meet the requirements of:

- a **Mack** GO-J fluid
- **Rockwell** 0-76D (SAE 80W-90), 0-76-A (SAE 85W-140)

### TYPICAL TEST DATA

SAE Grade	80W-90	85W-140
Product Number	222316	222317
MSDS Number	8628	8628
API Gravity	28.4	25.9
Viscosity, Kinematic cSt at 40°C cSt at 100°C	145 14.2	341 25.0
Viscosity, Saybolt SUS at 100°F SUS at 210°F	762 76.4	1819 124
Viscosity, Brookfield cP at -12°C cP at -26°C	- 118,000	102,000 -
Viscosity Index	95	95
Flash Point, °C(°F)	221(430)	229(444)
Pour Point, °C(°F)	-33(-27)	-15(+5)

Typical test data are average values only. Minor variations which do not affect product performance are to be expected in normal manufacturing.