



SHELL NAUTILUS[®] 2-CYCLE ENGINE OIL

Premium, high performance, ashless lubricant

Product Description

Shell Nautilus[®] 2-Cycle Engine Oil is a premium quality, high performance, ashless two-cycle motor oil for water-cooled and air-cooled engines. Shell Nautilus[®] 2-Cycle Engine Oil is formulated for use in both premix and oil injected systems (see table below). It is dyed blue for easy identification.

Product Applications

- meets the warranty requirements for water-cooled two-cycle engines manufactured by Chrysler, Evinrude, Force, Johnson, Mariner, Mercury, OMC, Suzuki and Yamaha
- Suitable for motorcycles, lawn mowers, snowmobiles, personal watercraft, snow blowers, chain saws, and other air-cooled two-cycle engines JASO FB or API Service Category TC quality

Approvals and Recommendations

- NMMA TC-W3[®]
- TC-WII, TC-W (obsolete)
- API TC
- JASO FB

Table 1/ Gasoline to Oil Ratio

Gallons of Gasoline	Gasoline To Oil Ratio						
	16:1	20:1	24:1	32:1	40:1	50:1	100:1
	Ounces of Oil To Be Added						
1	8	6	5	4	3	3	1.5
3	24	19	16	12	10	8	4
6	48	38	32	24	19	16	8

Shell Nautilus[®] 2-Cycle Engine Oil should be used at the engine manufacturer's recommended fuel/oil ratio.

Table 2/Typical Properties of Shell Nautilus[®] 2-Cycle Engine Oil

	Test Method	
Product Code		55485
Color	Visual	Blue
Viscosity @ 40°C, cSt @ 100°C, cSt	D 445 D 445	49.6 8.3
Flash Point, PMCC, °F	D93	203
Sulfated Ash, wt%	D874	None

Handling & Safety Information

For information on the safe handling and use of this product, refer to its Material Safety Data Sheet at <http://www.shell-lubricants.com/msds/>. If you are a Shell Distributor, please call **1+800-468-6457** for all of your service needs. All other customers, please call **1+800-840-5737** for all of your service needs. Information is also available on the World Wide Web: <http://www.shell-lubricants.com/>.